



Technical data sheet Compleo GO

Technical Data Compleo G0

Construction type	Wallbox or charging column
Number of charging points	1
Charging capacity per charging point	3,7 - 11 kW
Voltage	230 / 400 V
Amperage	16 A
Phases	1-3 Phases
Authorization	Plug & Charge
Charging socket	No
Charging cable	Type 2, firmly attached, 5 m
Dimensions wallbox (H x W x D)	386 x 295 x 117 mm
Weight wallbox	8 kg
Dimensions charging column (H x W x D)	1370 x 250 x 180 mm
Weight charging column	11,5 kg
Load contactor	Relay
Control fuse	No
Integrated fuses	Residual current detection, AC 30 mA, DC 6 mA
RCD (required in sub-distribution)	FI Type A
Circuit breaker (required in sub-distribution)	max C 16 A
DC tripping current $I_{\Delta dc}$	0,006 A
Housing lockable	No
Energy meter	No
Adjustable	No
Storage temperature	-25 to 40 °C
Operating temperature	-25 to 40 °C
Protection class	1
Protection degree	IP54
Rated voltage U_n	230 V / 400 V 1/3 AC
Rated current I_n	up to 16 A adjustable from 6 A to 16 A in 2 A steps
Nominal frequency f_n	50 Hz
Overvoltage category	III
System according to type of earth connection	TN

Installation site	private, semi-public
EMC classification	EN 61000-6-2, EN 61000-6-3
Standards	DIN EN IEC 61851-1 DIN EN 61851-22
Directives	Low Voltage Directive 2014/35/EU
Compliant with calibration law	No
Data storage	No
Manufacturer	Compleo Connect GmbH
Origin	Germany

©2021 Compleo. All rights reserved.

This document may not be copied or reproduced in any form or by any means, in whole or in part, without written permission. All illustrations in this technical data sheet serve only as examples and may differ from the delivered product. All information in this manual is subject to change without notice and does not represent a commitment on the part of the manufacturer.



Contact

Compleo Connect GmbH
Paderborner Straße 76
D-33189 Schlangen

T: +49 5252 9889220
info@compleo-cs.com
www.compleo-cs.com

Technical changes and errors are reserved.
Ver. 20210709