



Technical data sheet

Compleo PRO plus

Technical Data Compleo PRO plus

Construction type	Wallbox or charging column
Number of charging points	2
Charging capacity per charging point	3,7 - 22 kW
Voltage	230 / 400V
Amperage	16 / 32A
Phases	1-phase / 3-phase
Authorization	App, RFID
Charging socket	Type 2
Charging cable	Type 2, firmly attached
Dimensions wallbox (H x W x D)	560 x 560 x 220 mm
Weight wallbox	approx. 18,5 kg
Dimensions charging column (H x W x D)	1455 x 770 x 189 mm
Weight charging column	approx. 33 kg
Grid connection	-
Load contactor	4-pole, 40 A
Control fuse	1-pole, B6
Integrated fuses	RCM-module – DC fault current detection 6 mA, contactor monitoring, Lock release module
RCD	Not integrated (required in sub-distribution, recommended protection: type A 0,03 A / 40 A)
Maximum back-up fuse	Not integrated (required in sub-distribution, recommended protection: B16 A for 11 kW / B32 A for 22 kW)
DC tripping current $I_{\Delta dc}$	0,006 A
Housing lockable	Double-bit lock
Energy meter	Yes
OCPP connections	OCPP 1.6 JSON
Interfaces (internal)	RS485
Interfaces (external)	Ethernet RJ45, GSM / UMTS
Logs (internal)	Modbus RTU
Logs (external)	Modbus TCP, OCPP 1.6 JSON
Adjustable	Yes (digital input, Modbus TCP and OCPP 1.6 JSON)
State according to EN 61851-1	State D with ventilation is not supported.
Storage temperature	-30 to +70 °C
Operating temperature	-25 to +55 °C

Rel. humidity	5 to 95 % (non-condensing)
Protection class	1
Protection degree	IP54
Mechanical impact protection	IK 8
Rated voltage Un	230 / 400 V AC
Rated operational voltage Ue	220 / 380 - 240 / 415 V 3N
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4 kV
Overvoltage category	Category III
Rated current of a circuit Inc	Load side 16 A fused, control side 6 A fused Load side 32 A fused, control side 6 A fused
Rated peak withstand current Ipk	<6 kA
Rated short-time withstand current Icw	6 A
Rated conditional short-circuit current Icc	16 A, 32A
Rated frequency fn	50 Hz
Pollution degree	3
System according to type of earth connection	TN or TT
Installation site	Indoor and outdoor installation
EMC classification	Class B
Standards	EN IEC 61851-1, EN 61439-7, EN IEC 61000-6-2, EN 61000-6-3
Directives	Low Voltage Directive 2014/35/EU EMC-Directive 2014/30/EU RoHS Directive 2011/65/EU WEEE-Directive 2012/19/EU
Compliant with calibration law	No
Data storage	No
Manufacturer	Compleo Connect GmbH
Origin	Germany

©2022 Compleo. All rights reserved.

This document may not be copied or reproduced in any form or by any means, in whole or in part, without written permission. All illustrations in this technical data sheet serve only as examples and may differ from the delivered product. All information in this manual is subject to change without notice and does not represent a commitment on the part of the manufacturer.



Contact

Compleo Connect GmbH
Paderborner Straße 76
D-33189 Schlangen

T: +49 5252 9889220
info@compleo-cs.com
www.compleo-cs.com

Technical changes and errors are reserved.
Ver. 20210709