

BIG 5 Quickview



eBOX

Up to 22 kW charging capacity

AC charging
1x Type 2 Socket / Cable

Free charging

RFID

Smartphone-App

-

Optionally compliant
with calibration law

LAN

WLAN

Mobil data network

-

-

Wall mounted



DUO

Up to 22 kW charging capacity

AC charging
2x Type 2 Socket / Spiral cable

Free charging

RFID

Smartphone-App

-

Optionally compliant
with calibration law

LAN


-

Mobil data network

4,3" Display

Optionally Power-Rail Technology

Base mounted



DUO ims

Up to 22 kW charging capacity

AC charging
2x Type 2 Socket

Free charging

RFID

Smartphone-App

Giro- & Kreditkarte

Compliant
with calibration law

LAN

-

Mobil data network

4,3" Display

-

Base mounted



CITO 500

Up to 50 kW charging capacity

AC & DC charging
1x Type 2 Socket, 1x CCS cable

Free charging

RFID

Smartphone-App

Giro- & Kreditkarte

Optionally compliant
with calibration law

LAN

-

Mobil data network

4,3" Display

-

Base mounted



eTower 200

Up to 200 kW charging capacity

DC charging
2x CCS cable

Free charging

RFID

Smartphone-App

Giro- & Kreditkarte

Compliant
with calibration law

LAN

-

Mobil data network

15" Display

-

Base mounted

BIG 5 Detail view

	eBOX prof.	eBOX prof. (EKA)	eBOX prof. (cable)	eBOX prof. (cable EKA)	DUO Outdoor	DUO Outdoor (SAM)	DUO fleet	DUO fleet (SAM)	DUO fleet (cable)	DUO fleet (cable SAM)	DUO ims (DPZ)	DUO ims (1x BKE-I)	DUO ims (2x BKE-I)	DUO ims (KWM)	DUO ims plus (DPZ)	DUO ims plus (2x BKE-I)	CITO 500 (SAM)	CITO 500 (SAM PT)	CITO 500 (EU)	CITO 500 (EU PT)
Max. charging capacity AC (in kW)	22	22	22	22	22	22	22	22	11	11	22	22	22	22	22	22	22	22	22	22
Max. charging capacity DC (in kW)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	50	50	50	50
Number of charging points AC	1	1	1	1	2	2	2	2	2	2	2	2	2	2	2	2	1	1	1	1
Number of charging points DC	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1	1	1	1

Characteristics

Type 2 socket	●	●	-	-	●	●	●	●	-	-	●	●	●	●	●	●	●	●	●	●
Type 2 charging cable	-	-	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Type 2 spiral cable	-	-	-	-	-	-	-	-	●	●	-	-	-	-	-	-	-	-	-	-
CCS charging cable	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●
Free charging	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Authorize via RFID	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Authorize via smartphone app	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
ISO 15118 ready	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Giro-e	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	○	○	○	○
Payment Terminal	-	-	-	-	-	-	-	-	-	-	●	●	●	●	-	-	-	●	-	●
Calibration law-compliant with SAM	-	-	-	-	-	●	-	●	-	●	●	●	●	●	●	●	●	●	-	-
Calibration law-compliant via OCMF	-	●	-	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Display	-	-	-	-	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Ocpp 1.6 JSON	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
4G modem	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Power Rail Technology	-	-	-	-	-	-	●	●	●	●	-	-	-	-	-	-	-	-	-	-
Ethernet switch	-	-	-	-	-	-	●	●	●	●	-	-	-	-	-	-	-	-	-	-
RCD type A	-	-	-	-	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
DC residual current detection	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
MID-compliant meter (AC)	○	●	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
DC-meter	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●
Type 1+2+3 surge protection	-	-	-	-	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Ducto configuration interface	-	-	-	-	●	●	●	●	●	●	●	●	●	●	●	●	-	-	-	-
eConfig configuration interface	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Backend connection	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●
Load management	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	○	○	○	○
Wall mounted version	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
base mounted version	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1x BKE-I for eHZ	-	-	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-	-	-
2x BKE-I for eHZ	-	-	-	-	-	-	-	-	-	-	-	-	●	-	-	●	-	-	-	-
Three-point meter panel	-	-	-	-	-	-	-	-	-	-	●	-	-	-	●	-	-	-	-	-
House connection box	-	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-	-	-	-
Transformer metering	-	-	-	-	-	-	-	-	-	-	-	-	-	●	-	-	-	-	-	-
Ambient lighting	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●	●	●	●
Locking cylinder	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Double lock	-	-	-	-	-	-	-	-	-	-	●	●	●	●	●	●	-	-	-	-